ACTIK® Steel Skid Plate for Oil Pan

Installation & Use Instructions:

For '07 - Current Jeep® Wrangler (JK 2 and 4 Door)

AWARNING A

TO REDUCE RISK OF SERIOUS INJURY OR PROPERTY DAMAGE: READ ALL SAFETY MESSAGES, ALWAY WEAR

SAFETY GLASSES, AND UNDERSTAND ALL INSTRUCTIONS AND PROCEDURE NOTICES BEFORE ATTEMPTING TO INSTALL OR USE THIS PRODUCT.

AWARNING A

THE VEHICLE MUST BE PROPERLY SUPPORTED BY A VEHICLE LIFT OR JACK STANDS BEFORE BEGINNING

INSTALLATION. NEVER WORK UNDER A VEHICLE SUPPORTED ONLY BY A JACK. READ THE INSTRUCTIONS AND CONFIRM YOU HAVE THE PROPER TOOLS AND SKILLS TO COMPLETE THE JOB. CONTACT A PROFESSIONAL INSTALLER IF YOU DO NOT HAVE THE NECESSARY QUALIFICATIONS.

ACAUTION A GLASSES MUST BE WORN AT ALL


RISK OF EYE INJURY! SAFETY TIMES WHILE INSTALLING OR

MAINTAINING THIS PRODUCT. TORQUE AND RECHECK FASTENERS AFTER 250 MILES AND FREQUENTLY THEREAFTER. DO NOT USE IF DAMAGED.

AN AUXILLARY SKID PLATE ADDS EXTRA PROTECTION ON THE TRAIL. BUT IT CAN NOT GUARANTEE

AGAINST ALL POSSIBLE DAMAGE FROM LARGE OBJECTS YOU MAY ENCOUNTER. ALWAYS DRIVE WITH RESPECT FOR OBJECTS AND TERRAIN THAT COULD DAMAGE SENSITIVE PARTS OF THE VEHICLE.








A Few Words About Product Safety:

Your Tactik® Skid Plate is intended to enhance the performance and protection of your off road capable vehicle. Before installation, please review the following safety information and installation recommendations.

Throughout these instructions important safety information is generally preceded by one of three signal words indicating the relative risk of injury, property damage or adverse consequence.


The Signal Words Mean:



Before You Begin Installation:

Congratulations on your purchase of TacTik® Skid Plate for your Jeep® Wrangler. This custom fit skid plate has been designed for protection, long life, and great looks. When unpacking, check to make sure all parts are included and not damaged due to shipping.

If any part is missing or broken, please call Customer Service at 800-745-6037 as soon as possible. Thank you again for your purchase and let's start the installation process.




WHILE INSTALLING SKID PLATES, VISUALLY SCAN FOR ANY INTERFERENCE WITH DRIVETRAIN COMPONENTS AND/OR EXHAUST COMPONENTS AND THE SKID PLATE.

IF THERE IS ANY INTERFERENCE, ADJUST THE SKID PLATE ACCORDINGLY TO MAKE SURE ALL COMPONENTS ARE NOT TOUCHING. FAILURE TO DO THIS STEP MAY CAUSE DAMAGE TO THE VEHICLE.



PARTS LIST

- A) Oil Pan Skid Plate QTY 1
- B) Front Mounting bracket driver side QTY1
- C) Nut Plate QTY 1
- D) Front Mounting bracket passenger side QTY1
- E) M12 x 35mm washer QTY 4
- F) M12 x 25mm Hex Bolt QTY 1
- G) M12 Lock Washer QTY 4
- H) M10 x 1.5 x 25mm Bolts QTY 4
- I) M10 Lock Washers QTY 4
- J) M10 Flat Washers QTY 4
- K) M10 x 1.5 Nuts QTY 4




REQUIRED TOOLS

Safety Glasses 17mm Socket 18mm Socket Torque Wrench (ft lbs)

STEP 1

Put on safety glasses. Locate the factory transfer case skid plate (1-A) and factory transmission cross brace (1-B) (auto-matic only) and the Remove the factory fasteners with 17 and 18mm sockets. [FIG 1]

Note: You will not be reusing the factory transmission cross brace (1-B).






STEP 2


A) Locate the Right-side motor mount inside the frame rails (above the upper control arm) [FIG 2]. Install the mounting bracket (D) with the bends close to the ends. The slotted end mounts to the outside (bottom) of the motor mount with M10 hex bolt (H), lock washer (I) and flat washers (J). The end with the weld nut will be installed on the inside of the skid plate.

B) Locate the Left-side motor mount inside the frame rails (above the upper control arm). Install the mounting bracket (B) with the bends in the middle. The end with the weld nut will be installed on the inside of the motor mount and secured with an M10 hex bolt (H), lock washer (I) and flat washers (J). The slotted end mounts to the outside (bottom) of skid plate with M10 hex bolt (H), lock washer (I) and flat washers (J).



STEP 3

Install the Oil pan skid plate (A) to the brackets using the M10 Hex bolts (H), flat washer (J), lock washers (I) and M10 nuts (K) [FIG 3]



STEP 4

To mount the back of the skid plate, first slide the nut plate (C) inside the frame to the first opening [FIG 4].






STEP 5

Mount the back of the skid plate to the cross member using 2 - M12 hex bolts (F), lock washers (G) and M12 x 35mm washers (E) to secure the first 2 holes. [FIG 5]

STEP 6

Reinstall the factory transfer case skid plate (1-A) on top of the new oil pan skid plate using the factory M12 bolts.



Torque M10 bolts to 36 ftlbs and M12 bolts to 48 ftlbs.

Istallation is complete.







TACTIK® Exclusive One Year Limited Warranty

Your TACTIK® branded accessories are covered by the following Limited Warranty provided exclusively by TACTIK® located at 1028 Saunders Lane, West Chester PA 19380.

This **Limited Warranty** is the only warranty made in connection with your purchase. TACTIK® neither assumes nor authorizes any vendor, retailer or other person or entity to assume for it any other obligation or liability in connection with this product or **Limited Warranty**.

What is Covered: Subject to the terms, exclusions and limitations herein and with respect only to TACTIK® branded accessories first sold in the United States, TACTIK® warrants to the initial retail purchaser only that your TACTIK® accessory shall be free of defects in material and workmanship: for a period of one (1) year from date of retail purchase.

This **Limited Warranty** is not assignable and shall terminate upon sale of the vehicle upon which the TACTIK® accessory is installed or other transfer to third persons.

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability or fitness for a particular purpose on this product is limited to one (1) year from date of initial retail sale. TAC-TIK® reserves the rights to: (a.) require invoice or other proof your accessory is within the terms of this **Limited Warranty** as a condition of warranty service and, (b.) make future revisions to this product and **Limited Warranty** without prior notice or obligation to upgrade your product.

What is Not Covered:

Your TACTIK® **Limited Warranty** does not cover products or parts that TACTIK® determines have been damaged by or subjected to: (a.) installation damage, alteration, modification, combination with other parts, failure to maintain or improper repair or service, (b.) normal wear & tear, cosmetic damage or damage from moisture or water immersion, (c.) Acts of God, accidents, misuse, negligence, inadequate mounting or impact with vehicle(s), obstacles or other aspects of the environment, (d.) theft, vandalism or other intentional damage.

Remedy Limited to Repair/Replacement: The exclusive remedy provided hereunder shall, upon TACTIK's inspection and at TACTIK's option, be either repair or replacement of product or parts (new or refurbished) covered under this Limited Warranty. Customers requesting warranty consideration should first contact TACTIK® to obtain a RGA number via telephone at 800-603-4064, or initiate customer service by email at: customerservice@tactik4x4.com. All labor, removal, shipping and installation costs are customer's responsibility.

Other Limitations - Exclusion of Damages - Your Rights Under State Law:

In consideration of the purchase price paid, neither TACTIK® nor any independent TACTIK® distributor/licensee are responsible for any time loss, rental costs, or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. Your exclusive remedy hereunder for covered parts is repair/replacement as described above.

This **Limited Warranty** gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and /or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

©TACTIK® 2021 All Rights Reserved. A4 Version

Instructions Part #12999.3194

